



ALPHA

engineered composites

145 Lehigh Avenue, Lakewood, NJ 08701
T: 732.634.5700 **F:** 732.634.1430 alphainc.com

ALPHA STYLE 9678-VS-2				
<u>DESCRIPTION</u> Alpha Style 9678-VS-2 is a medium weight vinyl coated fiberglass.				
<u>APPLICATIONS</u> Style 9678-VS-2 is designed for use as a core material for flexible duct applications and can also be used as a facing material for sound attenuating blankets and many other applications.				
PROPERTY DATA STYLE 9678-VS-2				
CHARACTERISTIC	METHOD	VALUES*		
		ENGLISH		METRIC
WEIGHT	ASTM-D-3776	6.5 oz/sy ± 10%		221 g/m ² ± 10%
THICKNESS	ASTM-D-1777	0.006" ± .10%		0.152 mm ± 10%
TENSILE STRENGTH	ASTM-D-5035	Warp-	125 lbs/inch	22.33 kg/cm
		Fill-	120 lbs/inch	21.43 kg/cm
TEAR STRENGTH	ASTM-D-1424	Warp-	88.18 oz.	2500 gms.
		Fill-	105.82 oz.	3000 gms.
MULLEN BURST	ASTM-D-3786	275 psi		19.25 kg/cm ²
FLAME RESISTANCE	ASTM D-6413	Char Length	1 inch max.	2.54 cm max.
		Afterglow	1 sec. max.	1 sec. max.
		Flame Out	0 sec. max.	0 sec. max.
ABRASION RESISTANCE	ASTM-D-3389	Wheel-H22 Load-500g Revolutions-250		
		End Point - Break in Yarns		
Color		Silver		

DATA SHEET: 12843 REV: C DATE: 03/05/12 *All values are nominal unless otherwise specified.

Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.