



1

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Alpha Style 1675/9480 BH PS
Common Name: Fiberglass/ Foil laminate with adhesive
SDS Number: 0756
Revision Date: 2/9/2018

Supplier Details: Alpha Engineered Composites LLC.
145 Lehigh Avenue
Lakewood, NJ 08701

Contact: James Palmer
Phone: 732-634-5700
Fax: 732-634-1430
Email: jpalmer@alphainc.com
Internet: www.alphainc.com

Classification of Substance**GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):**

Health, Specific target organ toxicity - Single exposure, 3
 Health, Skin corrosion/irritation, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING

GHS Hazard Pictograms:

**GHS Hazard Statements:**

H335 - May cause respiratory irritation
 H315 - Causes skin irritation

GHS Precautionary Statements:

P264 - Wash _ thoroughly after handling.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: This material may enter the body through inhalation of nuisance dust.
Target Organs: Respiratory system
Inhalation: Sore, raspy throat
Skin Contact: Redness and possible rash; itching
Eye Contact: Itching and redness
Ingestion: N/A

Chemical Ingredients		
CAS#	%	Chemical Name
65997-17-3		Fibrous Glass
7429-90-5	20-26.5%	Aluminum Foil
51-79-6	6.5-7.7%	Urethane Adhesive
9003-01-4	32.5-38.8%	Acrylic Adhesive
63394-02-5		Silicone Coated Paper

Fibrous Glass (CAS 65997-17-3)

Exposure Limits: OSHA PEL 15 mg/m³ (total), 5 mg/m³ (respirable). ACGIH TLV 1 f/cc (30-36.5%)

Inhalation: Remove person to fresh air. If condition persists, seek medical attention.
Skin Contact: Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.
Eye Contact: Rinse with water. Do not rub eyes. Seek medical attention.
Ingestion: Not applicable.

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

Material is a solid in roll form. If accidentally released, rewind material back onto roll.

Handling Precautions: Use adequate material handling equipment.

Storage Requirements: Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.

Engineering Controls: Local exhaust; dust collection

Personal Protective Equipment: HMIS PP, A | Safety Glasses

Safety glasses; cotton gloves; long sleeve clothing

Wash thoroughly with soap and water after handling

Appearance: Aluminized Fabric Tape

Physical State: Solid

Odor: No Odor

Specific Gravity or Density: 2.2

Solubility: Negligible

Boiling Point: N/A

Freezing or Melting Point: > 500 F

Vapor Pressure: N/A

Vapor Density: N/A

Potentia Hydrogenii: N/A

Chemical Stability: Material is stable.

Conditions to Avoid: None known.

Materials to Avoid:

Materials to Avoid: Strong oxidizing agents.

Hazardous Decomposition: Carbon monoxide; carbon dioxide; nitrogen oxide; cyanide

Hazardous Polymerization: Will Not Occur.

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

Incineration preferred in a federal, state, or local approved facility.

None special required.

Component (CAS#) [%] - CODES

Fibrous Glass (65997-17-3) [n/a%] TSCA

Aluminum Foil (7429-90-5) [20-26.5%] EPCRAWPC, MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR
RQ(100LBS), Urethane Adhesive (51-79-6) [6.5-7.7%] CERCLA, HAP, MASS, NJHS, NRC, PA, PROP65,
SARA313, TSCA, TXAIR, TXHWL

Acrylic Adhesive (9003-01-4) [32.5-38.8%] TSCA

Silicone Coated Paper (63394-02-5) [n/a%]


Regulatory CODE Descriptions

RQ = Reportable Quantity
TSCA = Toxic Substances Control Act
EPCRAWPC = EPCRA Water Priority Chemicals
MASS = MA Massachusetts Hazardous Substances List
NJHS = NJ Right-to-Know Hazardous Substances
OSHA WAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals
TXAIR = TX Air Contaminants with Health Effects Screening Level
CERCLA = Superfund clean up substance
HAP = Hazardous Air Pollutants
NRC = Nationally Recognized Carcinogens
PROP65 = CA Prop 65
TXHWL = TX Hazardous Waste List


NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = None

HMIS III: Health = 1(Chronic), Fire = 0, Physical Hazard = 0

HMIS PPE: A - Safety Glasses



HMIS	
HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	A



Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extended no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).