



1

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Alpha Style FB 1102
Common Name: Fluoroelastomer Belt
SDS Number: 0783
Revision Date: 2/9/2018
Product Use: Expansion Joints

Supplier Details: Alpha Engineered Composites LLC.
145 Lehigh Avenue
Lakewood, NJ 08701

Contact: James Palmer
Phone: 732-634-5700
Fax: 732-634-1430
Email: jpalmer@alphainc.com
Internet: www.alphainc.com

Classification of Substance**GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):**

Health, Skin corrosion/irritation, 3
 Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING

GHS Hazard Pictograms:

**GHS Hazard Statements:**

H316 - Causes mild skin irritation
 H335 - May cause respiratory irritation

GHS Precautionary Statements:

P264 - Wash _ thoroughly after handling.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: This material may enter the body through inhalation of nuisance dust.
Target Organs: Respiratory system
Inhalation: Sore, raspy throat
Skin Contact: Redness and possible rash; itching
Eye Contact: Itching and redness
Ingestion: N/A

Chemical Ingredients		
CAS#	%	Chemical Name
0		Inconel
0		Compounded Fluoroelastomer Rubber
65997-17-3		Fibrous Glass

Fibrous Glass (CAS 65997-17-3)

Exposure Limits: OSHA PEL 15 mg/m³ (total), 5 mg/m³ (respirable) ACGIH TLV 1 f/cc

Inhalation: Remove person to fresh air. If condition persists, seek medical attention.
Skin Contact: If fibers irritate the skin wash with soap and water
Eye Contact: Flush eyes with water for 15 minutes or until fibers are removed.
Ingestion: Not applicable.

5

FIRE FIGHTING MEASURES

Flammability: N/A

Lower Explosive Limit: N

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A **UEL:** N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes. Use self contained breathing apparatus above 570F

Unusual Fire and Explosion Hazards: None

6

ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidentally released, rewind material back onto roll.

7

HANDLING AND STORAGE

Handling Precautions: Use adequate material handling equipment.

Storage Requirements: Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Local exhaust; dust collection

Personal Protective Equipment: HMIS PP, B | Safety Glasses, Gloves

Safety glasses; cotton gloves; long sleeve clothing or face shields, as necessary

Wash thoroughly with soap and water after handling

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black Rubber continuous belt

Physical State: Solid

Specific Gravity or Density: 2.6

Boiling Point: N/A

Vapor Pressure: N/A

Potentia Hydrogenii: N/A

Odor: No Odor

Solubility: Negligible

Freezing or Melting Point: N/A

Vapor Density: N/A

10

STABILITY AND REACTIVITY

Chemical Stability: Material is stable.

Conditions to Avolentification: None known.

Materials to Avolentification: None reasonably foreseeable

Hazardous Decomposition: Oxides of carbon, hydrogen fluoride

Hazardous Polymerization: Will Not Occur.

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

{\rtf1\ansi\deff0{\fonttbl{\f0\fnil\charset0 Arial;}}
 \viewkind4\uc1\pard\lang1033\fs20 Incineration preferred in a federal, state, or local approved facility.
 \par }

None special required.

Component (CAS#) [%] - CODES

 Inconel (0) [n/a%]


Compounded Fluoroelastomer Rubber (0) [n/a%]

Fibrous Glass (65997-17-3) [n/a%] TSCA


Regulatory CODE Descriptions

 TSCA = Toxic Substances Control Act

NFPA: Health = 3, Fire = 0, Reactivity = 0, Specific Hazard = n/a
HMIS III: Health = 2, Fire = 0, Physical Hazard = 0
HMIS PPE: B - Safety Glasses, Gloves



HMIS	
HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B



Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).