



ALPHA

engineered composites

145 Lehigh Avenue, Lakewood, NJ 08701
T: 732.634.5700 **F:** 732.634.1430 alphainc.com

ALPHA - WELD STYLE 2150 WELDGARD				
<u>DESCRIPTION</u> Alpha Style 2150 WELDGARD is made of 100% glass yarns and treated with a special acrylic `orange coating. It is designed to help reduce lint and increase workability of cloth. Base fabric is designed to resist intermittent temperatures up to 1000F. ANSI/FM 4950 approved for welding curtains.				
<u>APPLICATIONS</u> Safety Apparel, Gaskets, Blankets, Insulation for Piping, Curtains, Stress Relieving and Heat Shields.				
PROPERTY DATA STYLE 2150 WELDGARD				
<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>		
		<u>ENGLISH</u>		<u>METRIC</u>
WEIGHT	ASTM-D-3776	24 oz/sy +/- 10%		815 g/m ² ± 10%
THICKNESS	ASTM-D-1777	0.050" +/- 10%		1.27 mm +/- 10%
TENSILE STRENGTH	ASTM-D-579	Warp- 400 lbs min. Fill- 400 lbs min.		71.44 kg/cm 71.44 kg/cm
TEMPERATURE RESISTANCE		1000 °F (Base Fabric - Intermittent)		538° C
CONSTRUCTION		15 (W) x 8 (F)		
COLOR		Orange		
CHEMICAL RESISTANCE: resists most acids and alkalis, except Hydrofluoric and hot phosphoric acids. Unaffected by bleaches or solvents. Won't rot or mildew.				

DATA SHEET: 13724 FM REV: G DATE: 4/21/2017 *All values are nominal unless otherwise specified.

Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.