



GHS Safety Data Sheet

Alpha Engineered Composites

Alpha Style 2025/9383-A

1	PRODUCT AND COMPANY IDENTIFICATION
Product Identifier: Common Name: SDS Number: Revision Date:	Alpha Style 2025/9383-A Fiberglass Fabric 0758 2/9/2018
Supplier Details:	Alpha Engineered Composites LLC. 145 Lehigh Avenue Lakewood, NJ 08701
Contact: Phone: Fax: Email:	James Palmer 732-634-5700 732-634-1430 jpalmer@alphainc.com
Internet:	www.alphainc.com

SDS Number: 0758

Classification of Substance

2

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Respiratory or skin sensitization, 1 Skin

Health, Skin corrosion/irritation, 2

Health, Serious Eye Damage/Eye Irritation, 2 B

Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING

GHS Hazard Pictograms:



GHS Hazard Statements:

H317 - May cause an allergic skin reaction

- H315 Causes skin irritation
- H320 Causes eye irritation
- H335 May cause respiratory irritation

GHS Precautionary Statements:

P264 - Wash _ thoroughly after handling. P333+313 - If skin irritation or a rash occurs: Get medical advice/attention. P337 - If eye irritation persists: _ P337+313 - Get medical advice/attention.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry:	This material may enter the body through inhalation of nuisance dust.
Target Organs:	Respiratory System;
Inhalation:	Sore, raspy throat.
Skin Contact:	May cause irritation, tearing and redness.
Eye Contact:	May Cause Irritation.
Ingestion:	Ingestion is not applicable route of entry for intended use.
3	COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients			
CAS#	%	Chemical Name	
65997-17-3		Fibrous Glass	
0		Acrylic Coating	

Fibrous Glass (CAS 65997-17-3) Exposure Limits: OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable). ACGIH TLV 1 f/cc

FIRST AID MEASURES

Inhalation:	Remove person to fresh air. If condition persists, seek medical attention.
Skin Contact:	Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.
Eye Contact:	Rinse with water. Do not rub eyes. Seek medical attention.
Ingestion:	Not applicable.

4

6

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposiiton of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidently released, rewind material back onto roll.

7	HANDLING AND STORAGE
Handling Precautions: Storage Requirements:	Use adequate material handling equipment. Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.
8	EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	Local exhaust; dust collection	
Personal Protective	HMIS PP, B Safety Glasses, Gloves	
Equipment:	Safety glasses; cotton gloves; long sleeve clothing	
Wash thoroughly with soap and water after handling		

9	PHYSICAL AND CHEMICAL PROPERTIES		
Appearance:	Tan Fabric		
Physical State:	Solid	Odor:	No odor
Specific Gravity or Density:	2.5	Solubility:	Negligible
Boiling Point:	N/A	Freezing or Melting Point:	> 1000 F
Vapor Pressure:	N/A	Vapor Density:	N/A
Potentia Hydrogenii:	N/A		

STABILITY AND REACTIVITY

Chemical Stability:	Material is stable.
Conditions to Avoldentification:	None known.
Materials to Avoldentification:	Strong oxidizing agents.
Hazardous Decomposition:	Carbon monoxide; carbon dioxide
Hazardous Polymerization:	Will Not Occur.

TOXICOLOGICAL INFORMATION

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

10

11

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

13 DISPOSAL CONSIDERATIONS

Incineration perferred in a federal, state, or local approved facility.

14

12

TRANSPORT INFORMATION

None special required.

15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Fibrous Glass (65997-17-3) [n/a%] TSCA


Acrylic Coating (0) [n/a%]

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act

16 OTHER INFORMATION

NFPA:Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = n/aHMIS III:Health = 1(Chronic), Fire = 0, Physical Hazard = 0HMIS PPE:B - Safety Glasses, Gloves



Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).