



# GHS Safety Data Sheet

**Alpha Engineered Composites** 

Alpha Weld 35 GR

1	PRODUCT AND COMPANY IDENTIFICATION	_
Product Identifier: Common Name: SDS Number: Revision Date:	Alpha Weld 35 GR Fiberglass Fabric 0531 2/9/2018	
Supplier Details:	Alpha Engineered Composites LLC. 145 Lehigh Avenue Lakewood, NJ 08701	
Contact: Phone: Fax: Email: Internet:	James Palmer 732-634-5700 732-634-1430 jpalmer@alphainc.com www.alphainc.com	

## **Classification of Substance**

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Respiratory or skin sensitization, 1 Skin

Health, Skin corrosion/irritation, 2

Health, Serious Eye Damage/Eye Irritation, 2 B

Health, Specific target organ toxicity - Single exposure, 3

### **GHS Label Elements, Including Precautionary Statements**

#### GHS Signal Word: WARNING

#### GHS Hazard Pictograms:



#### **GHS Hazard Statements:**

H317 - May cause an allergic skin reaction

H315 - Causes skin irritation

H320 - Causes eye irritation

H335 - May cause respiratory irritation

#### **GHS Precautionary Statements:**

P264 - Wash \_ thoroughly after handling. P333+313 - If skin irritation or a rash occurs: Get medical advice/attention. P337 - If eye irritation persists: \_ P337+313 - Get medical advice/attention.

### Hazards not Otherwise Classified (HNOC) or not Covered by GHS

3	COMPOSITION/INFORMATION ON INGREDIENTS
Ingestion:	N/A
Eye Contact:	Itching and redness
Skin Contact:	Redness and possible rash; itching
Inhalation:	Sore, raspy throat
Target Organs:	Respiratory system
Route of Entry:	This material may enter the body through inhalation of nuisance dust.

Chemical Ingredients		
CAS#	%	Chemical Name
65997-17-3		Fibrous Glass

### Fibrous Glass (CAS 65997-17-3) Exposure Limits: OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable). ACGIH TLV 1 f/cc

# 4 FIRST AID MEASURES Inhalation: Remove person to fresh air. If condition persists, seek medical attention. Skin Contact: Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention. Eye Contact: Rinse with water. Do not rub eyes. Seek medical attention. Ingestion: Not applicable.

6

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposiiton of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

# ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidently released, rewind material back onto roll.

7	HANDLING AND STORAGE
Handling Precautions: Storage Requirements:	Use adequate material handling equipment. Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.
8	EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	Local exhaust; dust collection	
Personal Protective	HMIS PP, B   Safety Glasses, Gloves	
Equipment:	Safety glasses; cotton gloves; long sleeve clothing	
Wash thoroughly with soap and water after handling		

9	PHYSICAL AND CHEMICAL PR	OPERTIES	
Appearance:	White Fabric		
Physical State:	Solid	Odor:	No Odor
Specific Gravity or Density:	2.5	Solubility:	Negligible
Boiling Point:	N/A	Freezing or Melting Point:	> 1000 F
Vapor Pressure:	N/A	Vapor Density:	N/A
Potentia Hydrogenii:	N/A		

STABILITY AND REACTIVITY

Chemical Stability:	Material is stable.
Conditions to Avoldentification:	None known.
Materials to Avoldentification:	Strong oxidizing agents.
Hazardous Decomposition:	Carbon monoxide; carbon dioxide
Hazardous Polymerization:	Will Not Occur.

# **TOXICOLOGICAL INFORMATION**

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

10

11

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

13 DISPOSAL CONSIDERATIONS

Incineration perferred in a federal, state, or local approved facility.

14

TRANSPORT INFORMATION


None special required.

15	REGULATORY INFORMATION	
Component (CAS#) [%] - CODES		
Fibrous Glass (65997-17-3) [n/a%] TSCA		
Regulatory CODE Descriptions		
TSCA = Toxic Substances Control Act		

# 16 OTHER INFORMATION

NFPA: HMIS III: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = n/a Health = 1(Chronic), Fire = 0, Physical Hazard = 0

HMIS PPE: B - Safety Glasses, Gloves



#### Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose (s).