

SDS

GHS Safety Data Sheet

Alpha Engineered Composites

Alpha Maritex Style 8451 SR

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Alpha Maritex Style 8451 SR **Common Name:** Silicone Coated Glass Fabric

SDS Number: 0053 **Revision Date:** 1/31/2018

Supplier Details: Alpha Engineered Composites LLC.

145 Lehigh Avenue Lakewood, NJ 08701

 Contact:
 James Palmer

 Phone:
 732-634-5700

 Fax:
 732-634-1430

Email: jpalmer@alphainc.com **Internet:** www.alphainc.com

2 HAZARDS IDENTIFICATION

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 3

Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING

GHS Hazard Pictograms:



GHS Hazard Statements:

H316 - Causes mild skin irritation H335 - May cause respiratory irritation

GHS Precautionary Statements:

P264 - Wash _ thoroughly after handling.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: This material may enter the body through inhalation of nuisance dust.

Target Organs:Respiratory SystemInhalation:Sore, raspy throat

Skin Contact: Redness and possible rash; itching

Eye Contact: Itching and redness

Ingestion: N/A

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients		
CAS#	%	Chemical Name
65997-17-3	-	Fibrous Glass
_	-	Compounded silicone coating

Fibrous Glass (CAS 65997-17-3)

Exposure Limits: OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable). ACGIH TLV 1 f/cc

SDS Number: 0053 Page: 1 / 3 Revision Date: 1/31/2018

4 FIRST AID MEASURES

Inhalation: Remove person to fresh air. If condition persists, seek medical attention.

Skin Contact: Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.

Eye Contact: Rinse with water. Do not rub eyes. Seek medical attention.

Ingestion: Not applicable.

5

FIRE FIGHTING MEASURES

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and

fumes.

Unusual Fire and Explosion Hazards: None

6

ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidently released, rewind material back onto roll.

7 HANDLING AND STORAGE

Handling Precautions: Use adequate material handling equipment.

Storage Requirements: Store in dry place. Use may be at temperature extremes based on product data, but storage should be

No Odor

Negligible

at ambient temperature.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Local exhaust; dust collection

Personal Protective HMIS PP, B | Safety Glasses, Gloves

Equipment: Safety glasses; cotton gloves; long sleeve clothing

Wash thoroughly with soap and water after handling

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Reddish Orange Coated Fabric

Physical State: Solid Odor:
Specific Gravity or 2.4 Solubility:

Density:

Boiling Point:

N/A

Boiling Point: N/A Freezing or Melting > 1000 F

Point:

Vapor Pressure: N/A Vapor Density: N/A

Potentia Hydrogenii: N/A

10

STABILITY AND REACTIVITY

Chemical Stability: Material is stable. **Conditions to** None known.

Avoldentification:

Materials to Avoldentification: Strong oxidizing agents.

Hazardous Decomposition: Carbon monoxide; carbon dioxide

Hazardous Polymerization: Will Not Occur.

SDS Number: 0053 Page: 2 / 3 Revision Date: 1/31/2018

11 TOXICOLOGICAL INFORMATION

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

12 ECOLOGICAL INFORMATION

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

13 DISPOSAL CONSIDERATIONS

Incineration perferred in a federal, state, or local approved facility.

14 TRANSPORT INFORMATION

None special required

15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Fibrous Glass (65997-17-3) [n/a%] TSCA

Compounded silicone coating (0) [n/a%]

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act

16 OTHER INFORMATION


NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = None

HMIS III: Health = 1, Fire = 0, Physical Hazard = 0

HMIS PPE: B - Safety Glasses, Gloves







Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

SDS Number: 0053 Page: 3 / 3 Revision Date: 1/31/2018